



AUN/SEED-Net



8th **AUN/SEED-Net** REGIONAL CONFERENCE ON ELECTRICAL AND ELECTRONICS ENGINEERING

Envision, Enable, and Empower
Smarter and Resilient Societies

co-located with

11th **ERDT Conference** on Semiconductor and Electronics, Information and Communications Technology and Energy

16-17 November 2015
Metro Manila, Philippines



**Proceedings of the 8th AUN/SEED-Net RCEEE 2015 and 11th ERDT Conference
on Semiconductor and Electronics, Information and Communications Technology, and Energy**

Editors:

Dr. Joel Joseph S. Marciano Jr.

Dr. Jhoanna Rhodette I. Pedrasa

Dr. Rhandley D. Cajote

© Copyright 2015 by the Electrical and Electronics Engineering Institute, College of Engineering, University of the Philippines Diliman, Engineering Research and Development for Technology, and ASEAN University Network/Southeast Asia Engineering Education Development Network (AUN/SEED-Net).

All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form without the consent of the editors of the Proceedings of the 8th AUN/SEED-Net RCEEE 2015 and 11th ERDT Conference on Semiconductor and Electronics, Information and Communications Technology, and Energy.

ISBN: 978-616-406-075-3

Published by: ASEAN University Network / Southeast Asia Engineering Education Development Network
(AUN/SEED-Net) JICA Project
Faculty of Engineering, Bldg. 2
Chulalongkorn University, Bangkok
Thailand 10330

Printed in the Philippines by: ERZALAN PRINTING PRESS
45 Cotabato Street, Luzviminda Village, Batasan Hills, Quezon City, Philippines

8th AUN/SEED-Net Regional Conference on Electrical and Electronics Engineering 2015

co-located with

11th ERDT Conference on Semiconductor and Electronics, Information and Communications Technology, and Energy

Envision, Enable and Empower Smarter and Resilient Societies

Published by: ASEAN University Network / Southeast Asia Engineering Education
Development Network (AUN/SEED-Net) in partnership with Engineering Research and
Development for Technology (ERDT) and University of the Philippines Diliman.

© Copyright 2015

No part of this publication may be reproduced without the consent of the editors of the
Proceedings of the 8th AUN/SEED-Net Regional Conference on Electrical and Electronics
Engineering 2015 and 11th ERDT Conference on Semiconductor and Electronics, Information
and Communications Technology, and Energy.

ISBN: 978-616-406-075-3

ENERGY PROFILING USING A BUILDING ENERGY MONITORING SYSTEM

Rafael Mizar L. Zita, John Kevin B. Ellamil, and Jhoanna Rhodette I. Pedrasa*

Electrical and Electronics Engineering Institute
University of the Philippines Diliman, PHILIPPINES.
*E-mail: jipedrasa@upd.edu.ph

ABSTRACT

With the rising cost of fossil fuel and the need to decrease our carbon footprint, reducing energy use has become imperative. This is especially true for large consumers wherein the electric bill accounts for a significant percentage of the organization's operating expenses. Executives, building owners and administrators, however, typically do not have the information they need to make informed, proactive decisions about their facility's energy use. Research have shown that providing more detailed feedback to consumers of their energy usage can significantly reduce electrical consumption [1, 2]. A Building Energy Monitoring System (BEMS) is one such system that can provide this information. A BEMS gathers real-time energy consumption of branch circuits in building and allows users to plot this information for further analysis. BEMS are commercially available already, although such systems are typically very expensive.

A prototype of a low-cost BEMS was developed in a previous project undertaken at UP-EEEI. This work builds on that system by improving on the security aspects of the system and increasing the accuracy of the energy measurements by lowering the error from 8% in the previous work to 3% (or 97% accuracy). Additionally, the hardware modules are deployed at the University of Philippines, Diliman EEE Institute building for three months to characterize and build an energy profile of the usage of facilities in the EEE Institute.

Security was improved by migrating the embedded system hardware from Gizduino X to Arduino Yun. RSA-2048 encryption was then implemented to secure the messages from the branch meter data loggers to the centralized server. The communication between users and the web server was also secured by using the HTTPS protocol for all web accesses.

To improve the accuracy of the power and energy measurements, the calibration procedure was changed. Instead of a single value used as the set point, multiple test points with known loads were used and a python script was incorporated in the web server to automatically calculate the piecewise equation per metering channel. This resulted in improving the accuracy of the measurements in the whole range of operation from 1 to 15 Amperes. It also made it easier to perform the re-calibration procedure as the values are not hard-coded on the Arduino boards anymore and the function is performed by the server instead.

Table 1 shows the average percentage error of power as measured from eight randomly selected branch meters. The meters were attached to a known load, and the load was varied every 15 minutes from 0A to 15A (1A load change per 15 minutes over a period of 4 hours. The power readings as measured by the meters were then noted, and compared to a commercially available power meter which served as the ground truth for comparison. The data shows that the average error is 1.29%, which is within the target 3% error range of this project.

Table 1: Average % Error (Power)

Meter Number	Averag % Error	Std Deviation
Meter 1	0.81	1.89
Meter 2	1.24	2.37
Meter 5	1.29	2.99
Meter 6	1.20	2.84
Meter 7	1.47	3.24
Meter 8	1.42	4.07
Meter 11	1.57	3.52
Meter 12	1.32	3.19
Average % Error	1.29	3.01

Four 16-circuit BEMS modules were implemented and deployed at each floor of the old wing of the EEEI Building. Circuits monitored include convenience outlets, lighting, and air-conditionaing units of various research and instructional laboratories of the second, third and fourth floors. Data gathering commenced in August and will continue for three months to October. Preliminary results should be available by November 2015.

Keywords: energy profile, building energy monitoring

Acknowledgment

This work was funded by UP Diliman Office of the Vice Chancellor for Research and Development Source of Solutions Grant.

References

- [1] X. F. Jiang, "A high-fidelity energy monitoring and feedback architecture for reducing electrical consumption in buildings," Ph.D. dissertation, EECS Department, University of California, Berkeley, September 2010. [Online]. Available: <http://www.eecs.berkeley.edu/Pubs/TechRpts/2010/EECS-2010-125.html>
- [2] A. Hashizume, T. Mizuno, and H. Mineno, "Energy monitoring system using sensor networks in residential houses," in 26th International Conference on Advanced Information Networking and Applications Workshops (WAINA 2012), March 2012, pp. 595 –600.