



AUN/SEED-Net



8th **AUN/SEED-Net** REGIONAL CONFERENCE ON ELECTRICAL AND ELECTRONICS ENGINEERING

Envision, Enable, and Empower
Smarter and Resilient Societies

co-located with

11th **ERDT Conference** on Semiconductor and Electronics, Information and Communications Technology and Energy

16-17 November 2015
Metro Manila, Philippines



**Proceedings of the 8th AUN/SEED-Net RCEEE 2015 and 11th ERDT Conference
on Semiconductor and Electronics, Information and Communications Technology, and Energy**

Editors:

Dr. Joel Joseph S. Marciano Jr.

Dr. Jhoanna Rhodette I. Pedrasa

Dr. Rhandley D. Cajote

© Copyright 2015 by the Electrical and Electronics Engineering Institute, College of Engineering, University of the Philippines Diliman, Engineering Research and Development for Technology, and ASEAN University Network/Southeast Asia Engineering Education Development Network (AUN/SEED-Net).

All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form without the consent of the editors of the Proceedings of the 8th AUN/SEED-Net RCEEE 2015 and 11th ERDT Conference on Semiconductor and Electronics, Information and Communications Technology, and Energy.

ISBN: 978-616-406-075-3

Published by: ASEAN University Network / Southeast Asia Engineering Education Development Network
(AUN/SEED-Net) JICA Project
Faculty of Engineering, Bldg. 2
Chulalongkorn University, Bangkok
Thailand 10330

Printed in the Philippines by: ERZALAN PRINTING PRESS
45 Cotabato Street, Luzviminda Village, Batasan Hills, Quezon City, Philippines

8th AUN/SEED-Net Regional Conference on Electrical and Electronics Engineering 2015

co-located with

11th ERDT Conference on Semiconductor and Electronics, Information and Communications Technology, and Energy

Envision, Enable and Empower Smarter and Resilient Societies

Published by: ASEAN University Network / Southeast Asia Engineering Education
Development Network (AUN/SEED-Net) in partnership with Engineering Research and
Development for Technology (ERDT) and University of the Philippines Diliman.

© Copyright 2015

No part of this publication may be reproduced without the consent of the editors of the
Proceedings of the 8th AUN/SEED-Net Regional Conference on Electrical and Electronics
Engineering 2015 and 11th ERDT Conference on Semiconductor and Electronics, Information
and Communications Technology, and Energy.

ISBN: 978-616-406-075-3

PROCESSING AND PROPERTIES OF $\text{Li}_7\text{La}_3\text{Zr}_2\text{O}_{12}$ Li-Ion CONDUCTING SOLID ELECTROLYTE FOR LITHIUM-ION BATTERIES

Shari Ann Botin^{1*} and Rinlee Butch Cervera²

¹Energy Engineering Program, College of Engineering,
University of the Philippines Diliman, PHILIPPINES

²Department of Mining, Metallurgical and Materials Engineering, College of Engineering,
University of the Philippines Diliman, PHILIPPINES
E-mail: botinshariann@gmail.com

ABSTRACT

$\text{Li}_7\text{La}_3\text{Zr}_2\text{O}_{12}$ (LLZ) solid electrolytes were synthesized via conventional solid state reaction using different temperatures. Characterization was carried out for crystal structure (XRD), ionic conductivity (EIS) and surface morphology (SEM). XRD results show that sintering at higher temperature favors the formation of cubic LLZ and increases the stability of LLZ pellets. Moreover, the study identified 1150°C as an optimum sintering temperature that obtained a relatively high ionic conductivity $8.15 \times 10^{-5} \text{ Scm}^{-1}$ at room temperature. The increase in ionic conductivity is also attributed to its high relative density value of 92.88%. The study suggests that low ionic conductivity of LLZ is caused mainly by poor crystal structure, low relative density, and the impurities present in LLZ pellet.

Keywords: Ionic Conductivity, $\text{Li}_7\text{La}_3\text{Zr}_2\text{O}_{12}$, Lithium-ion Battery, Solid Electrolyte

Introduction

Solid electrolytes have long been a demand for lithium-ion batteries to replace organic liquid electrolytes due to flammability and stability issues. The challenge lies on the discovery of solid electrolytes that possess both high ionic conductivity and good chemical stability against other metals which can improve the high energy density requirement of lithium-ion batteries suitable for electric vehicles and energy storage applications. One good example is $\text{Li}_7\text{La}_3\text{Zr}_2\text{O}_{12}$ (LLZ) which is proven to possess both properties. ^[1] This study aims to characterize LLZ solid electrolytes synthesized at varying temperatures.

Methodology

LLZ was synthesized via conventional solid-state reaction. Stoichiometric amounts of Li_2CO_3 (Techno Pharmchem, 99.5%; dried at 180°C for 6 h; 10 wt% was added to compensate for Li losses), La_2O_3 (Techno Pharmchem, 99%; dried at 900°C for 2h) and ZrO_2 (Emfutur, 97.2%; dried at 180°C for 6 h) were ground using agate mortar and then calcined at 900°C for 2h. The powder mixture were pelletized and sintered at 1000°C, 1150°C and 1200°C for 36 h using alumina crucibles. In addition, sintering at 1150°C for 15 h was also carried out to investigate the effect of sintering duration on the relative density of LLZ pellet. The sintered LLZ pellets were characterized for its structure (XRD), ionic conductivity (EIS) and surface morphology (SEM).

Results and Discussions

Figure 1 shows the effect of sintering temperature on the structure of LLZ pellets. Tetragonal LLZ is formed from 1000°C to 1150°C while cubic LLZ is formed at 1200°C. In addition, increasing the temperature stabilizes the tetragonal LLZ as depicted by the narrowing and reduction of splitting of peaks.

